

## 1. Identification of the substance/preparation and company/undertaking

<b>Product name</b>	<b>Castrol Classic XL 30</b>
<b>SDS no.</b>	452259
<b>Product use</b>	Automotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
<b>Supplier</b>	Castrol (UK) Ltd Wakefield House Pipers Way Swindon Wiltshire SN3 1RE
<b>EMERGENCY TELEPHONE NUMBER</b>	Carechem: +44 (0) 208 762 8322 (24 hours)

## 2. Composition/information on ingredients

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

**This product does not contain any hazardous ingredients at or above regulated thresholds.**

## 3. Hazards identification

This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

<b>Physical/chemical hazards</b>	Not classified as dangerous.
<b>Human health hazards</b>	Not classified as dangerous.
<b>Environmental hazards</b>	Unlikely to be harmful to aquatic organisms.

### Effects and symptoms

<b>Eyes</b>	No significant health hazards identified.
<b>Skin</b>	No significant health hazards identified.

### USED ENGINE OILS

Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

<b>Inhalation</b>	No significant health hazards identified.
<b>Ingestion</b>	No significant health hazards identified.

## 4. First-aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Get medical attention if irritation occurs.
<b>Skin contact</b>	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
<b>Inhalation</b>	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
<b>Ingestion</b>	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.
<b>Notes to physician</b>	Treatment should in general be symptomatic and directed to relieving any effects.

## 5. Fire-fighting measures

### Extinguishing media

<b>Suitable</b>	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
<b>Not suitable</b>	Do not use water jet.

**Hazardous decomposition products** Decomposition products may include the following materials:  
carbon oxides

**Special fire-fighting procedures** None identified.

**Protection of fire-fighters** Fire-fighters should wear self-contained positive pressure breathing apparatus (SCBA) and full turnout gear.

**Product name** Castrol Classic XL 30

**Product code** 452259-GB05

**Page:** 1/4

**Version** 2

**Date of issue** 13 August 2007

**Format** United Kingdom  
(UK)

**Language** ENGLISH

**Build** 8.2.4

(United Kingdom)

( ENGLISH )

## 6. Accidental release measures

<b>Personal precautions</b>	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
<b>Environmental precautions and clean-up methods</b>	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Minimize contact of spilled material with soils to prevent runoff to surface waterways. See Section 13 for Waste Disposal Information.
<b>Personal protection in case of a large spill</b>	Splash goggles. Full suit. Boots. Gloves.

## 7. Handling and storage

<b>Handling</b>	Wash thoroughly after handling.
<b>Storage</b>	Keep container tightly closed. Keep container in a cool, well-ventilated area.
<b>Not suitable</b>	Prolonged exposure to elevated temperature.

## 8. Exposure controls/personal protection

<b>Ingredient name</b>	<b>Occupational exposure limits</b>
Base oil - unspecified	<b>EH40 (United Kingdom (UK)).</b> STEL: 10 mg/m <sup>3</sup> 15 minute(s). Form: Oil mist, mineral TWA: 5 mg/m <sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Whilst specific OELs for certain components are included in this SDS, it should be noted that other components of the preparation will be present in any mist, vapour or dust produced. For this reason, the specific OELs may not be applicable to the product and are provided for guidance purposes.

**Control Measures** Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.

All chemicals should be assessed for their risks to health and appropriate control measures put in place to prevent or adequately control exposure. A hierarchy of control measures exists (e.g. elimination, substitution, general ventilation, containment, systems of work, changing the process or activity) that must be considered before use of personal protective equipment. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

**Hygiene measures** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

### Personal protective equipment

#### Respiratory system

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn.

Air-filtering respirators, also called air-purifying respirators, will not be adequate under conditions of oxygen deficiency (i.e. low oxygen concentration), and would not be considered suitable where airborne concentrations of chemicals with a significant hazard are present. In these cases air-supplied breathing apparatus will be required.

Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

#### Skin and body

Use of protective clothing is good industrial practice.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

**Product name** Castrol Classic XL 30

**Product code** 452259-GB05

**Page:** 2/4

**Version** 2

**Date of issue** 13 August 2007

**Format** United Kingdom  
(UK)

**Language** ENGLISH

**Build** 8.2.4

(United Kingdom)

( ENGLISH )

<b>Hands</b>	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves.  Recommended: nitrile gloves  Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.
<b>Eyes</b>	Safety glasses with side shields.

## 9 . Physical and chemical properties

<b>Flash point</b>	211 °C (Closed cup) Pensky-Martens.
<b>Pour point</b>	27 °C
<b>Colour</b>	Amber.
<b>Odour</b>	Oily.
<b>Physical state</b>	Liquid.
<b>Density</b>	861 kg/m <sup>3</sup> (0.881 g/cm <sup>3</sup> ) at 15°C
<b>Solubility</b>	Insoluble in water.
<b>LogK<sub>ow</sub></b>	3
<b>Viscosity</b>	Kinematic: 99 mm <sup>2</sup> /s (99 cSt) at 40°C Kinematic: 11.05 mm <sup>2</sup> /s (11.05 cSt) at 100°C

## 10 . Stability and reactivity

<b>Incompatibility with various substances</b>	Reactive with oxidising agents.
<b>Hazardous polymerisation</b>	Will not occur.
<b>Hazardous decomposition products</b>	Decomposition products may include the following materials: carbon oxides

## 11 . Toxicological information

<b>Acute toxicity</b>	Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.  Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.  Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.  At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
<b>Chronic toxicity</b>	
<b>Other chronic toxicity data</b>	SED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
<b>Carcinogenic effects</b>	No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen by ACGIH, the International Agency for Research on Cancer (IARC) or the European Commission (EC).

## 12 . Ecological information

<b>Persistence/degradability</b>	Inherently biodegradable.
<b>Mobility</b>	Spillages may penetrate the soil causing ground water contamination.
<b>Bioaccumulative potential</b>	This product is not expected to bioaccumulate through food chains in the environment.
<b>Environmental hazards</b>	Unlikely to be harmful to aquatic organisms.
<b>Other ecological information</b>	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## 13 . Disposal considerations

<b>Disposal Consideration / Waste information</b>	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
---	---

<b>Product name</b> Castrol Classic XL 30	<b>Product code</b> 52259-GB05	<b>Page:</b> 3/4
<b>Version</b> 2	<b>Date of issue</b> 13 August 2007	<b>Format</b> United Kingdom (UK)
	<b>Build</b> 8.2.4	<b>Language</b> ENGLISH ( ENGLISH )

## 14 . Transport information

Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

## 15 . Regulatory information

### Label requirements

#### Risk phrases

This product is not classified according to the EU regulations.

#### EU regulations

Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EEC as amended and adapted.

### Other regulations

#### Inventories


 **Europe inventory:** All components are listed or exempted.

 **United States inventory (TSCA 8b):** All components are listed or exempted.


 **Australia inventory (AICS):** All components are listed or exempted.

 **Canada inventory:** All components are listed or exempted.

 **China inventory (IECSC):** All components are listed or exempted.

 **Japan inventory (ENCS):** At least one component is not listed.

 **Korea inventory (KECI):** All components are listed or exempted.

 **Philippines inventory (PICCS):** All components are listed or exempted.

## 16 . Other information

### History

**Date of issue** 13/08/2007.

**Date of previous issue** 29/09/2006.

**Prepared by** Product Stewardship Group

### Notice to reader

Revision Indicator: The presence of a triangle in the upper left corner of a field indicates a change since the previous version.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

**Product name** Castrol Classic XL 30

**Product code**  52259-GB05

**Page:** 4/4

**Version** 2

**Date of issue** 13 August 2007

**Format** United Kingdom  
(UK)

**Language** ENGLISH

**Build** 8.2.4

(United Kingdom)

( ENGLISH )